Luxxor® LTC Camera HD Color Video Camera





Overview

The New Luxxor® LTC Camera attaches to any Hawkeye® Rigid or Flexible Borescope, transforming it into a complete Video Borescope System. The system contains the New LTC HD video Camera with 3MP CMOS sensor and provides crystal clear images, 25mm Luxxor Video Coupler lens, and Video ToolBox Software. The camera offers both USB3 and HDMI outputs, and the Video Tool Box Software allows easy still image and video capture. It also includes a zoom feature, various cross hairs and grids, and image annotation.

Specifications

Image Sensor	1/3.2" 3mp Color CMOS Sensor
Effective Pixels	2304 x 1536
Frame Rate	HDMI: 1080i 60fps, USB: 720p 30fps
Video Output	USB3 and HDMI
AGC	Auto with adjustment

Lens Mount	C-Mount
Software	Video Toolbox (Image and Video Capture, crosshair/grid overlay, digital zoom)
Operating Temp	4 to 49 deg C (40 to 120 F)
Storage Temp	-30 to +60 deg C (-22 to +140F)
Dimensions	Call for information

Software

The LXC Camera includes Zarbeco™ Video Toolbox Pro Software

Software Features: Image and Video Capture Digital Zoom Image Labeling Crosshair/Grid Overlay Image Drawing



